

Numerical Index

2N2893-2N2967

TYPE	MATERIAL	POLARITY	REPLACE- MENT	PAGE NUMBER	USE	MAXIMUM RATINGS						ELECTRICAL CHARACTERISTICS							
						P _D	Ref Point	T _J	V _{CB}	V _{CE} -	Subscript	h _{FE} @ I _C		V _{CE(SAT)} @ I _C		h _{fT}	Subscript	f _T	Subscript
						@ 25°C	°C	(volts)	(volts)	(min)		(max)	Units	Units	Units				
2N2893	S	N		8-165	PMS	30W	C	200	100	80	O	50	150	1.0A	0.5	1.0A	50	E	30M
2N2894	S	N			MSS	360M	A	200	12	12	O	40	150	30M	0.15	10M		E	400M
2N2894A	S	P			PMS	360M	A	200	12	12	S	40	30M					E	800M
2N2895	S	N			MSA	500M	A	200	120	65	O	40	120	150M	0.6	150M	50	E	120M
2N2896	S	N			MSA	500M	A	200	140	90	O	60	200	150M	0.6	150M	50	E	120M
2N2897	S	N			MSA	500M	A	200	60	45	O	50	200	150M	1.0	150M	50	E	120M
2N2898	S	N			MSA	500M	A	200	120	65	O	40	120	150M	0.6	150M	50	E	120M
2N2899	S	N			MSA	500M	A	200	140	90	O	60	200	150M	0.6	150M	50	E	120M
2N2900	S	N			MSA	500M	A	200	60	45	O	50	200	150M	1.0	150M	50	E	120M
2N2901	S	N			CHP	0.36W	A	200	20	10	O	30		10M	0.15	10M		E	300M
2N2902	S	N		LPA	40W	C	200	120	120	O	30	90	500M	7.5	500M	30	E	2.0M	
2N2903	S	N	2N2917	11-27	DFA	600M	C	200	60	30	O	125	625	1.0M	1.0	5.0M	150	E	60M
2N2903A	S	N	2N2915	11-27	DFA	600M	C	200	60	30	O	125	625	1.0M	1.0	5.0M	150	E	60M
2N2904	S	N		HSS	3.0W	C	200	60	40	O	40	120	150M	0.4	150M		E	200M	
2N2905	S	N		HSS	3.0W	C	200	60	40	O	100	300	150M	0.4	150M		E	200M	
2N2905A	S	N		HSS	3.0W	C	200	60	40	O	100	300	150M	0.4	150M		E	200M	
2N2906	S	N		HSS	1.8W	C	200	60	40	O	40	120	150M	0.4	150M		E	200M	
2N2906A	S	N		HSS	1.8W	C	200	60	40	O	40	120	150M	0.4	150M		E	200M	
2N2907	S	N		HSS	1.8W	C	200	60	40	O	100	300	150M	0.4	150M		E	200M	
2N2907A	S	N		HSS	1.8W	C	200	60	40	O	100	300	150M	0.4	150M		E	200M	
2N2908	S	N		LPA	75W	C	200	80	60	R	12	60	1.0A	1.0	1.0A	10	E	1.0M	
2N2909	S	N		HSA	0.4W	A	200	60	40	O	40	120	0.15A	0.25	0.15A		E	50M	
2N2910	S	N	2N3409	11-33	DFA	0.3W	A	200	45	25	O	70		0.1M	1.0	10M	50	E	11M
2N2911	S	N	2N3766	7-142	PMS	5.0W	C	200	150	125	O	20	60	1.0A	0.3	1.0A		E	1.0M
2N2912	G	P		7-97	PMS	75W	C	110	15	6.0	O	75		1.0A	0.5	25A		E	20M
2N2913	S	N		11-27	DFA	300M	A	200	45	45	O	60	240	10*	0.35	1.0M		E	60M
2N2914	S	N		11-27	DFA	300M	A	200	45	45	O	150	600	10*	0.35	1.0M		E	60M
2N2915	S	N		11-27	DFA	300M	A	200	45	45	O	60	240	10*	0.35	1.0M		E	60M
2N2915A	S	N			AFA	300M	A	200	45	45	O						240	E	60M
2N2916	S	N		11-27	DFA	300M	A	200	45	45	O	150	600	10*	0.35	1.0M		E	60M
2N2916A	S	N			AFA	300M	A	200	45	45	O						600	E	60M
2N2917	S	N		11-27	DFA	0.3W	A	200	45	45	O	60	240	10*	0.35	1.0M		E	60M
2N2918	S	N		11-27	DFA	0.3W	A	200	45	45	O	150	600	10*	0.35	1.0M		E	60M
2N2919	S	N		11-27	DFA	0.3W	A	200	60	60	O	60	240	10*	0.35	1.0M		E	60M
2N2919A	S	N			AFA	300M	A	200	60	60	O						240	E	60M
2N2920	S	N		11-27	DFA	0.3W	A	200	60	60	O	150	600	10*	0.35	1.0M		E	60M
2N2920A	S	N			AFA	300M	A	200	60	60	O						600	E	60M
2N2921	S	N			AFA	0.2W	A	125	25	25	O						35	E	35
2N2922	S	N	MPS6512	5-109	AFA	0.2W	A	125	25	25	O						55	E	55
2N2923	S	N	MPS2923	5-84	AFA	0.2W	A	125	25	25	O						90	E	90
2N2924	S	N	MPS2924	5-84	AFA	0.2W	A	125	25	25	O						150	E	150
2N2925	S	N	MPS2925	5-84	AFA	0.2W	A	125	25	25	O						235	E	235
2N2926	S	N	MPS2926	5-85	AFA	0.2W	A	125	18	18	O						35	E	35
2N2927	S	P			MNS	800M	A	200	25	25	O	30	130	50M	0.25	50M		E	100M
2N2928	G	P			RFA	150M	A	100	15	13	O	0.8	200	2.0M	0.5	50M	0.10	E	400M
2N2929	G	P		9-33	RFA	750M	C	100	25	10	O	10	100	10M	0.25	100M		E	800M
2N2930	G	P	2N3427	6-41	MSS	250M	A	100	30	12	O	60	420	10M	0.25	100M		E	800M
2N2931	S	N			APC	50M	A	125	5.0	5.0	O	50	50M	0.45	50M		E	20M	
2N2932	S	N			AFC	50M	A	125	5.0	5.0	O	70	50M	0.45	50M		E	70	
2N2933	S	N			AFC	50M	A	125	5.0	5.0	O	50	50M	0.45	50M		E	45	
2N2934	S	N			AFC	50M	A	125	45	30	O	50	50M	0.45	50M		E	30	
2N2935	S	N			AFC	50M	A	125	45	30	O	70	50M	0.45	50M		E	70	
2N2936	S	N			LPA	300M	A	175	60	55	O	100	300	10*	0.3	2.0M	150	E	30M
2N2937	S	N			LPA	300M	A	175	60	55	O	100	300	10*	0.3	2.0M	150	E	30M
2N2938	S	N			HSS	300M	A	200	25	13	O	30	50M	0.4	50M		E	500M	
2N2939	S	N			HFA	0.8W	A	300	75	60	O	60	240	0.15A	0.75	0.15A		E	150M
2N2940	S	N			HFA	0.8W	A	300	120	80	O	60	240	0.15A	0.75	0.15A		E	150M
2N2941	S	N			HFA	0.8W	A	200	150	100	O	60	240	0.15A	0.75	0.15A		E	150M
2N2942	S	P			HSS	150M	A	100	50	25	O	50	10M	0.15	10M		E	150M	
2N2943	G	P			HSS	150M	A	100	30	15	O	30	10M	0.2	10M		E	120M	
2N2944	S	P			CHP	400M	A	175	15	10	O	80	1.0M					E	10M
2N2944A	S	P			CHP	400M	A	200	15	10	O	100	1.0M					E	15M
2N2945	S	P			CHP	400M	A	175	25	20	O	40	1.0M					E	5.0M
2N2945A	S	P			CHP	400M	A	200	25	20	O	100	1.0M					E	10M
2N2946	S	P			CHP	400M	A	175	40	35	O	30	1.0M					E	3.0M
2N2946A	S	P			CHP	400M	A	200	40	35	O	50	1.0M					E	5.0M
2N2947	S	N		9-35	MPA	25W	C	175	60	60	S	2.5	55	0.4A	0.5	1.0A		E	100M
2N2948	S	N		9-35	MPA	25W	C	175	40	40	S	2.5	100	0.4A	0.5	1.0A		E	100M
2N2949	S	N		9-38	MPA	6.0W	C	175	60	60	S	5.0	100	40M	0.5	0.4A		E	100M
2N2950	S	N		9-38	MPA	6.0W	C	175	60	60	S	5.0	100	40M	0.5	0.4A		E	100M
2N2951	S	N		9-40	MPA	3.0W	C	175	60	60	S	20	150	10M	0.5	0.15A		E	200M
2N2952	S	N		9-40	MPA	1.8W	C	175	60	60	S	20	150	10M	0.5	0.15A		E	200M
2N2953	G	P	2N1194	6-30	AFC	120M	A	100	30	25	R	100	50M				200	E	300M
2N2954	S	N			RFA	200M	A	200	30	20	O	25	300	2.0M			25	E	200M
2N2955	G	P		8-173	HSS	0.15W	A	100	4										